



- Gelato showcase with ventilated refrigeration available in 3 sizes.
- Automatic defrosting feature.
- One piece structure with ecological polyurethane insulation (HCFC & HFC free) with 60 mm thickness and 43 Kg/m³.
- Electronic control board and digital thermometer.
- Double glazed tempered curved glass with built in resistance for high humidity condensation.
- Tilt-up curved glazed glass via hydraulic pistons.
- Aesthetic design with curved front access for higher visibility.
- High energy saving with sliding rear Plexiglass doors.
- Interior LED light illumination.

Features	Prime 12 G	Prime 18 G	Prime 24 G
Dimension mm	1240 x 1505 x 1200	1760 x 1505 x 1200	2285 x 1505 x 1200
Pan Capacity Lt	12 x 5 lt - 8 x 7 lt	18 x 5 lt - 12 x 7 lt	24 x 5 lt - 16 x 7 lt
Power Consumption (Standard) W	1650 W	2400 W	3150 W
Power Consumption (Defrost) W	2530 W	3700 W	4960 W
Refrigerant	R404a	R404a	R404a
Operation Temperature °C	-18 / -22 °C	-18 / -22 °C	-18 / -22 °C
Power Supply	220 V / 1 Ph / 50 Hz	220 V / 1 Ph / 50 Hz	220 V / 1 Ph / 50 Hz
Compressor Type	Hermetic	Hermetic	Hermetic
Defrost	Automatic + Manuel	Automatic + Manuel	Automatic + Manuel
Defrost Type	Hot Gas	Hot Gas	Hot Gas

